



DW-ILWM1 - Mounting bracket for a single (1) NightWatch™ illuminator

- 'L' wall mount bracket for single illuminator.
- Compatible with all infra-red and white-light illuminators.
- Allows up to 180° rotation.
- Fully adjustable (left, right, up and down).
- Stainless steel construction (black powder coated).



DW-ILWM2 - Mounting bracket for two (2) NightWatch™ illuminators

- Dual illuminator mounting bracket compatible with all infra-red and white-light illuminators.
- Doubles the angle of illumination.
- Increases illumination distance by a factor of 1.4x when using two equivalent illuminators.
- Mix-and-match illuminators (angle and distance).
- Mix-and-match infra-red and white-light illuminators for a hybrid solution.
- Fully adjustable (left, right, up and down).
- Includes IP67 dust-tight and water-proof to 1 meter junction box.
- Stainless steel construction (black powder coated).



DW-ILWM3 - Mounting bracket for three (3) NightWatch™ illuminators

- Triple illuminator mounting bracket compatible with all infra-red and white-light illuminators.
- Triples the angle of illumination.
- Increases illumination distance by a factor of 1.7x when using three equivalent illuminators.
- Mix-and-match illuminators (angle and distance).
- Mix-and-match infra-red and white-light illuminators for a hybrid solution.
- Fully adjustable (left, right, up and down).
- Includes IP67 dust-tight and water-proof to 1 meter junction box.
- Stainless steel construction (black powder coated).



DW-ILPM1 - Pole-mount bracket for a single (1) NightWatch™ illuminator

- Single pole-mount bracket compatible with all infra-red and white-light illuminators and illuminator mounting brackets.
- Supplied with stainless steel straps to fit 2.95" to 7.87" (75mm to 200mm) diameter pole.
- Stainless steel construction.



Increase sales and profitability. Sign up and become a DW Channel Partner today!





DW-DTWT - Walk tester for SiteWatch™ motion detectors

An installation tool to help set up SiteWatch™ detectors on site.


- Power 9VDC (PP3 Cell).
- Current standby: 0.5mA.
- Operating: 30mA.
- Operating temperature: -4°F to +131°F (-20°C to +50°C).



DW-DTCAW - White conduit cable entry adaptor for SiteWatch™ motion detectors

For surface mount conduit and cable installations. Complete with integral wall tamper system.

- Suitable for 0.78" (20mm) conduit protected surface run cables.
- Integrated rear tamper mechanism designed to perfectly interface with rear tamper plunger fitted on all SiteWatch™ detectors.
- Supplied with body locking screws plus wall fixings.
- Dimensions: 5.7" x 4.7" x 1.7" (145 x 120mm x 44mm).
- Weight: 0.99 lbs (0.45 gr).



DW-DTPM - Pole mount clamp for SiteWatch™ motion detectors

For mounting SiteWatch™ detectors on poles from 1.57" to 6.69" (40mm to 170mm) in diameter, maximum two detectors per clamp kit.

- Two coated metal pole clamps c/w threaded bar and locking nuts and washers.
- Supplied with separate tamper-plate and fixing-screws.



Increase sales and profitability. Sign up and become a DW Channel Partner today!

